



MSDS – Material Safety Data Sheets

SECTION I: Product Identification

Product Name: EasyRock

Description: Molded polyurethane coated with blended Iron Oxides and Polymers

Manufacturer:

EasyRock USA Inc.
2260 S. Haven Ave., Unit B,
Ontario, California 91761

EasyRock Canada Inc.
13007 – 149 Street
Edmonton, AB T5L 2J7

Emergency Telephone No: (866) 985-5678

SECTION II: Hazardous Ingredients

Not Applicable. Rigid polyurethane is not considered or listed as a hazardous chemical.

SECTION III: Physical Properties

Appearance: Various formation, texture and color

Boiling Point (Degrees Fahrenheit): N/A

Specific Gravity (water = 1): 1.0

Vapor Density: N/A

Percent Volatile by Volume: 0

Melting point (Degrees Fahrenheit): N/A

Vapor Pressure: N/A

Solubility in Water: N/A

Evaporation Rate (butyl acetate): N/A

SECTION IV: Fire and Explosive Data

Flash Point: N/A

Auto Ignition Temperature: 500-550°F

Extinguishing Media: water, carbon dioxide, sand

Special Fire Fighting Procedures & Protective Equipment:

Firefighters and others who may be exposed to products of combustion should wear full protective clothing including self-contained breathing apparatus.

Unusual Fire & Explosion Hazards:

Sawing, sanding or machining can produce foam dust as a by-product which may present an explosion hazard if the dust cloud contacts an ignition source. An airborne concentration of 40 grams of dust per cubic meter of air is often used as the LEL for foam dust.

SECTION V: Reactivity Data

Conditions Contributing to Instability: stable under normal conditions

Incompatibility: Avoid contact with oxidizing agents. Avoid open flame. Product may auto-ignite at temperatures in excess of 450°F

Hazardous Decomposition Products: Thermal and/or thermal oxidative decomposition can produce irritating and toxic fumes and gasses including carbon monoxide, hydrogen cyanide